4A-55

Geopak Drainage - Pipes


Design Manual Chapter 4 Drainage

Originally Issued: 07-29-11 Revised: 11-30-11

This section provides instructions on how to add pipes in <u>Geopak Drainage</u>. In <u>Geopak Drainage</u>, pipes are called links.


Opening a Project

For instructions on Starting a new <u>Geopak Drainage</u> Project, see Section <u>4A-52</u>. To open an existing project, start <u>Geopak Drainage</u> as shown in Section <u>4A-52</u>. In the DRAINAGE dialog box, go to <u>Project Open</u> and browse to the appropriate file:



OR


Choose a project at the bottom of the Project menu in the DRAINAGE dialog box:




Adding Links

Links can be added in several ways:


• Using the Component menu in the DRAINAGE dialog box:



Using the Drainage Links toolbox accessed through the DRAINAGE dialog box:




The following tool box will appear:



• Using the Drainage Tool box accessed through the DRAINAGE dialog box:




The following tool box will appear:



• Using the Navigator accessed through the DRAINAGE dialog box:




The following dialog box will appear:



Regardless of the method designers use to add a link, the following dialog box will appear:



Click OK and the following dialog box will appear:



Definition

Under Options→ Definition

Type, Shape, Material, and Roughness: Set as shown in the dialog box above.


From Node and To Node: Click on the ID Node tools in and select the appropriate node (intake, junction/manhole, or outlet) in MicroStation for each.




Use the ID Node tool . If the ID Node tool is not used, <u>Geopak Drainage</u> will connect the pipe to the Location Station. This will cause the pipe length to be incorrect.

When selecting a node, click on a spot close to where the pipe should connect.

Note: Midpoint snaps are located on all sides of rectangular intakes and manholes (and at the upstream end of apron outlets), so snapping to a point is not necessary. When connecting pipes to circular intakes and manholes, <u>Geopak Drainage</u> will typically connect the pipe at the point closest to the structure to which the other end of the pipe connects.





Length: This will fill in automatically after the From Node and To Node have been selected.


Use MS Element: Toggling this on allows the designer to pick a MicroStation element to use as a link.

Design Size: Checking the box will allow <u>Geopak Drainage</u> to size the pipe. If the pipe has already been sized, do not check the box.

Number of Barrels: Set to 1.

Note: 2 barrels can be used where clearance issues exist or a larger capacity is needed; however, designers should first check to see if a pipe-arch can be used instead.

Clicking on the Select... button allows the designer to choose a pipe size and type. The following window will open:




Select the necessary pipe size and type, see Section 4A-10.

Conditions

Under Options → Conditions

Designers have two options: input calculated values for invert (flow line) elevations and pipe slopes, or allow <u>Geopak Drainage</u> to determine them. If inputting values, at least one invert elevation is required. The designer has the option of inputting either the second invert elevation or the pipe slope. To allow <u>Geopak Drainage</u> to design elevations and pipe slopes, leave all boxes unchecked.




- Invert:
 - o From Node: Input the Flow Line Inlet Elevation (Tab 104-5B).
 - To Node: Input the Flow Line Outlet Elevation (Tab 104-5B).
- Soffit: Input a calculated value for the pipe slope. Pipe slope fills in automatically if Flow Line Inlet and Flow Line Outlet are input.
- Min Cover: Elevations are set automatically by the pipe envelope in Preferences, see Section <u>4A-52</u>. Slope is based on difference in Min Cover elevation divided by distance between nodes.
- Max Depth: Elevations are set automatically by the pipe envelope in Preferences, see Section <u>4A-52</u>. Slope is based on difference in Max Depth elevation divided by distance between nodes.

Constraints

Under Options → Constraints


Fill out the window as follows:

- 1. *Rise*: This is the inside diameter of the pipe. Minimum pipe diameter is 15 inches (24 inches for Interstates). Maximum pipe diameter depends on the intake, see Standard Road Plans.
- 2. *Slope*: Minimum slope is 0.4%. There is no maximum slope; however, the pipe envelope (see Section 4A-53) will constrain maximum pipe slope. Maximum velocity may also constrain pipe slope.
- 3. *Velocity*: Minimum velocity is 3 ft/s and the maximum velocity is 15 ft/s.




Calculating Discharge

Under *Options* → *Computation*, the following window will appear:




This window will fill in when the network program is run, see Section <u>4A-56</u>. It will look similar to the window below:




Editing Links

Links can be edited at any time. Designers have several options to open a link for editing:

Using the <u>Component menu in the DRAINAGE dialog box:</u>



• Using the Drainage Links toolbox accessed through the DRAINAGE dialog box:



The following tool box will appear:




• Using the Drainage Tool Box accessed through the DRAINAGE dialog box:




The following tool box will appear:


Click on this icon and hold mouse button down until drop down menu appears




• Using the Navigator accessed through the DRAINAGE menu:



The following dialog box will appear:



Regardless of the method designers use edit a node, the Link Configuration Definition dialog box will appear:



Changes are made in this dialog box.

Note: In order to have changes take place, the Apply button must be clicked.

Chronology of Changes to Design Manual Section:

004A-055 Geopak Drainage – Pipes

11/30/2011 Revised

Correct graphics under Definition

7/29/2011 NEW

New