



PART PLAN VIEW




PART ELEVATION VIEW


PROVIDE 5 HOLES FORMED WITH 1" PLASTIC CONDUIT. COST TO BE INCLUDED IN PRICE BID FOR CONCRETE BARRIER RAILING.




VIEW G-G




SECTION B-B




SECTION C-C



SECTION D-D



PART VIEW E-E




PART VIEW F-F

NOTES:
THE 5c1, 6 - 5c2, 5c5-13, 2 - 5d2, 2 - 5d3 AND 4t1 BARS ARE TO BE PLACED WITH THE ABUTMENT WING FOOTING. THE DETAILS FOR PLACEMENT ARE SHOWN ON THE STANDARD ABUTMENT SHEET.

EPOXY REINFORCING STEEL - ONE END SECTION						
BAR	LOCATION	SHAPE	NO.	LENGTH	WEIGHT	
5c1	VERTICAL, RAIL TO WING FOOTING		34	2'-10"	100	
5c2	VERTICAL AT NOSE, RAIL TO WING FOOTING		9	2'-10"	27	
5c3	VERTICAL		17	6'-1"	108	
5c4	VERTICAL AT NOSE		3	2'-11"	9	
5c5-13	VERTICAL		9	VARIES	35	
4c14	VERTICAL		6	2'-6"	10	
5d1	HORIZONTAL		7	6'-8"	49	
5d2	HORIZONTAL		9	6'-9"	63	
5d3	HORIZONTAL		3	3'-5"	11	
4t1	WING FOOTING TIE BARS		10	VARIES	13	
(INCLUDE WITH BARRIER RAIL REINFORCING)					TOTAL WEIGHT (LBS.)	425

CONCRETE PLACEMENT SUMMARY		
SECTION		TOTAL
BARRIER RAIL ONE END SECTION		0.66 CU. YD.



NOTE: CONSTRUCTION JOINT BETWEEN TOP OF WING AND BARRIER RAIL SHALL BE ROUGHENED CONCRETE.

DASHED LINES BELOW THE TOP OF WING ARE THE ABUTMENT WING REINFORCING STEEL. SEE STANDARD ABUTMENT SHEETS FOR PLACEMENT.

THE 10" RADIUS AND 1 1/2" RADIUS ARE TYPICAL AND SHALL BE USED WHEN CONSTRUCTING THE CORNERS FOR VIEW A-A, SECTION B-B, SECTION C-C AND SECTION D-D.

FOR RUSTICATION IN WING SEE BT40-AS1-04 AND ABUTMENT AND MASKWALL DETAILS.

LATEST REVISION DATE APPROVED BY BRIDGE ENGINEER [Signature]		
	STANDARD DESIGN - 40' ROADWAY, 2 SPAN BRIDGES PRETENSIONED PRESTRESSED BULB TEE CONCRETE BEAM BRIDGES	
	ALL SPANS JULY, 2004	
	AESTHETIC BARRIER RAIL END SECTIONS DETAILS	BT40-BR1-04