




PART PLAN VIEW




PART VIEW E-E




PART ELEVATION VIEW
PROVIDE 5 HOLES FORMED WITH 1" PLASTIC CONDUIT. COST TO BE INCLUDED IN PRICE BID FOR CONCRETE BARRIER RAILING.




PART VIEW F-F




VIEW A-A



SECTION B-B



SECTION C-C



SECTION D-D


REINFORCING STEEL - ONE END SECTION

BAR	LOCATION	SHAPE	NO.	LENGTH	WEIGHT
5c1	VERTICAL, RAIL TO WING FOOTING		34	2'-10"	100
5c2	VERTICAL AT NOSE, RAIL TO WING FOOTING		12	2'-9"	34
5c3	VERTICAL		17	6'-1"	108
5c5-13	VERTICAL		9	VARIES	34
5d1	HORIZONTAL		7	6'-8"	49
5d2	HORIZONTAL		9	6'-9"	63
5d3	HORIZONTAL		3	3'-5"	11
4+1	WING FOOTING TIE BARS		10	VARIES	13
(INCLUDE WITH BARRIER RAIL REINFORCING)					TOTAL WEIGHT (LBS.) 412

CONCRETE PLACEMENT SUMMARY

SECTION	TOTAL
BARRIER RAIL ONE END SECTION	0.62 CU. YD.

BENT BAR DETAILS



NOTES:

CONSTRUCTION JOINT BETWEEN TOP OF WING AND BARRIER IS ROUGHENED CONCRETE.

THE 10" RADIUS AND 1 1/2" RADIUS ARE TYPICAL AND SHALL BE USED WHEN CONSTRUCTING THE CORNERS FOR VIEW A-A, SECTION B-B, SECTION C-C AND SECTION D-D.

THE 5c1, 6 - 5c2, 5c5-13, 2 - 5d2 AND 2 - 5d3 BARS ARE TO BE PLACED WITH THE ABUTMENT WING FOOTING. THE DETAILS FOR PLACEMENT ARE SHOWN ON THE LONGITUDINAL SECTION SHEET.

DASHED LINES BELOW THE TOP OF WING ARE THE ABUTMENT WING REINFORCING STEEL. SEE LONGITUDINAL SECTION SHEETS FOR PLACEMENT.

LATEST REVISION DATE :	STANDARD DESIGN - 24' ROADWAY, SINGLE SPAN BRIDGE
APPROVED BY :	PRETENSIONED PRESTRESSED CONCRETE BEAM BRIDGES
	JANUARY, 2005 HS20-44 LOADING
	IOWA DEPARTMENT OF TRANSPORTATION - HIGHWAY DIVISION
	BARRIER RAIL DETAILS SHEET 2 OF 3
	H24SI-32-05