## APPROVED SOURCES CONCRETE SEALERS FOR NON-TRAFFIC AREAS

\*All surfaces to be sealed must be sound, clean and DRY.

| MANUFACTURER                         | BRAND NAME              | COVERAGE RATE  | MIN. SURFACE<br>TEMP. °C (°F) |
|--------------------------------------|-------------------------|--|-------------------------------|
| Conspec                              | Spec-Seal               | 1 or 2 coats<br>2.5 m <sup>2</sup> /L<br>(100 ft. <sup>2</sup> /gal.)                  | 10 (50)                       |
| L & M Construction<br>Chemicals Inc. | Pentox 50               | 2 coats<br>1st coat 4.91 m <sup>2</sup> /L<br>(200 ft. <sup>2</sup> /gal.)             | 10 (50)                       |
|                                      |                         | 2nd coat 7.36 m <sup>2</sup> /L (300 ft. <sup>2</sup> /gal.)                           |                               |
| Poly-Carb, Inc.                      | Mark-124,<br>Mark-145   | 2 coats<br>1st coat Mark-124<br>2.70 m <sup>2</sup> /L<br>(110 ft. <sup>2</sup> /gal.) | 7 (45)                        |
|                                      |                         | 2nd coat Mark-145<br>2.95 m <sup>2</sup> /L<br>(120 ft. <sup>2</sup> /gal.)            |                               |
| Poly-Carb, Inc.                      | Mark-87                 | 2 coats<br>1st coat Mark-87<br>2.95 m <sup>2</sup> /L<br>(120 ft. <sup>2</sup> /gal.)  | 10 (50)                       |
|                                      |                         | 2nd coat Mark-87<br>2.45 m <sup>2</sup> /L<br>(100 ft. <sup>2</sup> /gal.)             |                               |
| Sika Chemical Company                | Sikadur 21 Lo-Mod<br>LV | 3.07 m <sup>2</sup> /L<br>(125 ft. <sup>2</sup> /gal.)                                 | 4 (40)                        |

| MANUFACTURER                       | BRAND NAME                       | COVERAGE RATE  | MIN. SURFACE<br>TEMP. °C (°F) |
|------------------------------------|----------------------------------|--|-------------------------------|
| Star, Inc.<br>(McConnell & Assoc.) | Macro-Dect                       | 7.36 m <sup>2</sup> /L<br>(80 ft. <sup>2</sup> /gal.)                          | 4 (40)                        |
| Steelcote Mfg. Company             | PE-50<br>Penetrating Sealer      | 1.96 m <sup>2</sup> /L<br>(80 ft. <sup>2</sup> /gal.)                          | 4 (40)                        |
| TK Products                        | TK-2671<br>Penetrating<br>Sealer | 2 coats<br>9.82 m <sup>2</sup> /L<br>(400 ft <sup>2</sup> /gal.)<br>each coat  | 4 (40)                        |
| Unitex                             | Bridge Seal                      | 1 coat<br>2.45 m <sup>2</sup> /L<br>(100 ft. <sup>2</sup> /gal.)               | 4 (40)                        |
| Viking Paints, Inc.                | TE-3008-1                        | 2 coats<br>9.82 m <sup>2</sup> /L<br>(400 ft. <sup>2</sup> /gal.)<br>each coat | 4 (40)                        |