



LEGEND

- 42" Channelizer or Vertical Panel
- × Drum
- ↳ Traffic Sign
- ▨ Work Area
- ← Direction of Traffic
- ▤▤▤▤ Arrow Panel

SPEED LIMIT (mph)	A	B	C	D	E	M
25 or less	300'	50'	40'	25'	80'	125'
30 - 35	500'	50'	80'	35'	160'	245'
40 - 45	700'	100'	80'	40'	400'	540'
50 - 55	1000'	100'	80'	40'	560'	680'
60 or longer	1000'	100'	80'	40'	720'	880'

- ① Place two drums in the closed lane at 1000-foot intervals. Where core outs, holes, or uncured concrete exists within the work area, place an additional pair of drums just ahead of each.
- ② Place the arrow panel behind the channelizing devices and as close to the beginning of the taper as practical.

Contract Item:
Traffic Control

<p>Iowa Department of Transportation</p> <p>STANDARD ROAD PLAN</p> <p>REVISIONS: Changed dual drum spacing to 1000 ft. Removed type III barricades. Modified speed limit table values and variables.</p> <p><i>Deanna Macfadyen</i> APPROVED BY DESIGN METHODS ENGINEER</p> <p>CLOSURE OF CONTINUOUS TWO WAY LEFT TURN LANE AND ADJACENT LANE</p>	REVISION	
	1	10-16-07
	TC-429	
	SHEET 1 of 1	