


- ① Trowel smooth and place 2 layers of 13.6 kg. roofing felt to prevent bond.
- ② Cast frame into intake top. See Standard Road Plan RA-66D for frame and grate details.
- ③ 920 mm maximum concrete pipe.
- ④ If intake base is precast, it shall be placed on a 150 mm bed of sand. This bedding shall be compacted and provide uniform support for the entire area of the base and shall extend 305 mm outside the edge of the base.
- ⑤ Top elevation of grates shall be 6 mm below Form Grade Elevation.
- ⑥ Possible subdrain. See plans for location and elevation. See Standard Road Plan RF-19C for connection details.
- ⑦ Bolt intake frames together on both sides with (4) 12.5 mm x 100 mm bolts.
- ⑧ Leave 75 mm opening through barrier over the intake.
- ⑨ Slope of top shall vary to match elevation of adjacent pavement.
- ⑩ Intake base may be cast in place or precast. If precast, the base and first wall section may be cast separately with a keyway or as one unit.

Steps, when specified, shall meet the requirements of ASTM C478. The top step shall be located a maximum of 711 mm below the form grade elevation.



Contract Items:

Barrier Intake, RA-47A

Tabulation: 104-5B



TYPICAL  
PAVEMENT JOINT LAYOUT DETAIL



For joint details,  
see Standard Road  
Plans RH-50, RH-51,  
and RH-52.

All dimensions given in millimeters unless noted.

<b>M</b> <b>METRIC VERSION</b>	Iowa Department of Transportation Highway Division		
	<b>STANDARD ROAD PLAN</b>		<b>RA-47A(1)</b>
	REVISION: NEW.		REVISION NO. NEW
	 APPROVED BY DESIGN METHODS ENGINEER		REVISION DATE 10-18-05
	<b>TRIPLE GRATE BARRIER INTAKE, RECTANGULAR</b> (Sheet 1 of 4)		