



**LEGEND**

- Traffic Sign
- Flagger
- Work Area
- Type III Barricade
- Direction of Traffic

SPEED LIMIT (mph)	A	F and G Range <sup>③</sup>	F + G Max.
35 or less	250'	250'-3250'	3500'
40 - 45	350'	350'-3350'	3700'
50 or greater	500'	500'-3500'	4000'

- ① A vehicle with an amber revolving light or amber strobe light may be substituted for the Type III barricade.
- ② Provide a second flagger if:  
 The flagger's view of approaching traffic in the open lane is less than 1/4 mile or the work site is in an area of restricted sight distance (such as a "No Passing" zone); or  
 Excessive traffic delays are encountered.
- ③ F and G distances are to remain as near minimum values as work permits. However, to be able to move the work area without moving the advance signing, F and G distances may be varied within the limits of the table. Maximum movement can be achieved by setting one F or G value at the minimum and the other value at its maximum.

Possible Contract Items:  
 Flaggers  
 Traffic Control

	REVISION
	4   04-16-13
<b>STANDARD ROAD PLAN</b>	<b>TC-212</b>
REVISIONS: Modified circle note 1.	SHEET 1 of 1
<i>Deanna Mufield</i> APPROVED BY DESIGN METHODS ENGINEER	
<b>SPOT LOCATION LANE CLOSURE        WITH FLAGGERS</b>	