



**LEGEND**

- ♩ Flagger
- Temporary Traffic Signal
- ↑ Traffic Sign
- 42" Channelizer
- ▨ Work Area
- ← Direction of Traffic

SPEED LIMIT (mph)	ADT	A	H
50 or greater	up to 2,500	500'	2.5 mi.
	2,500 - 5,000	500'	2.0 mi.
	more than 5,000	1000'	1.5 mi.

No detection area required.

Timing for Push-button Actuated Signals  
 Initial Green = 15 sec.  
 Green Ext. = 2.5 sec.  
 Yellow = 4.0 sec.

Install push-button actuated traffic signals.  
 Program signals to rest in RED.  
 GREEN and GREEN EXTENSION only are initiated by flagger.

- ① For Temporary Traffic Signals, meet the requirements of Section 2528.03 of the Standard Specifications except for the following:  
 In lieu of a trailer or span-wire mounted system, signal heads may be located on the shoulders, one on each side of the roadway. Mount shoulder signal heads a minimum of 8 feet from the bottom of the signal head to the top of the ground surface.
- ② Locate signal heads 70 to 100 feet beyond "STOP HERE ON RED" sign. Adjust location of signal heads as field conditions warrant.

Possible Contract Items:  
 Flagger  
 Pilot Car  
 Temporary Traffic Signal  
 Traffic Control

Possible Tabulations:  
 108-27  
 108-28

	REVISION
	4   10-20-15
STANDARD ROAD PLAN	TC-218
SHEET 1 of 1	
<small>REVISIONS: Added Flagger symbols, channelizer taper distance, and designer info button.</small>	
<small>APPROVED BY DESIGN METHODS ENGINEER</small>	
<p align="center"><b>LANE CLOSURE WITH                  PILOT CAR AND                  FLAGGER OPERATED SIGNALS</b></p>	