


TRANSITION DETAILS - TANGENT TO CURVE



TRANSITION DETAILS - SPIRAL CURVE

Refer to specific curve data contained in project plans for tangent runoff length (x), runoff length (L) and full superlevation (e).

When spiral curve transitions are not required:
Place 70% of full superlevation at the P.C. and P.T.
Place 30% of the runoff length within the curve.

Unless otherwise specified, all lengths are measured along the centerline of construction.

Superelevations on this standard are shown for curves to the right. Curves to the left are a mirror image of what is shown.

Smooth curves should be established at the time of construction at sections A-F along the profile edges of lines A-F.

See Detail A for profile grade location.

m = 30% of Runoff Length (L)

W = 48'

g = Normal Cross Slope (2.5%)

L = Distance to Change Cross Slope from 0% to e

e = Superelevation Rate


x = Distance to Change Cross Slope from 0% to 2.5%

s = Normal Shoulder Slope


① Spiral curve length coincides with runoff length (L)

Possible Tabulation:
101-18

| | |
|--|------------|
| | REVISION |
| | 1 10-16-18 |
| STANDARD ROAD PLAN | PV-306 |
| SHEET 1 of 4 | |
| <small>REVISIONS: Modified x dimension in DIAGRAMMATIC PROFILES OF THE PAVEMENT EDGE LINES on SHEET 4.</small> | |
| <small>APPROVED BY DESIGN METHODS ENGINEER</small> | |
| SUPERELEVATION DETAILS EIGHT LANE ROADWAY CLOSED MEDIAN | |




- ② High Side Shoulder: Maintain normal shoulder cross slope (s) until the cross slope break with the adjacent pavement reaches 8.0%, then slope the shoulder at the same rate as the adjacent pavement maintaining an 8% cross slope breakover.
- ③ Low Side Shoulder: Maintain normal shoulder cross slope (s) until the adjacent pavement slope equals s, then slope the shoulder at the same cross slope as the adjacent pavement.
- ④ Subgrade Surface: Subgrade surface cross slope parallel to pavement surface cross slope.




DETAIL A

| | |
|--|---------------|
| STANDARD ROAD PLAN | REVISION |
| | 1 10-16-18 |
| | PV-306 |
| | SHEET 2 of 4 |
| <small>REVISIONS: Modified x dimension in DIAGRAMMATIC PROFILES OF THE PAVEMENT EDGE LINES on SHEET 4.</small> | |
| <small>APPROVED BY DESIGN METHODS ENGINEER</small> | |
| SUPERELEVATION DETAILS EIGHT LANE ROADWAY CLOSED MEDIAN | |




- ② High Side Shoulder: Maintain normal shoulder cross slope (s) until the cross slope break with the adjacent pavement reaches 8.0%, then slope the shoulder at the same rate as the adjacent pavement maintaining an 8% cross slope breakover.
- ③ Low Side Shoulder: Maintain normal shoulder cross slope (s) until the adjacent pavement slope equals s , then slope the shoulder at the same cross slope as the adjacent pavement.
- ④ Subgrade Surface: Subgrade surface cross slope parallel to pavement surface cross slope.



| | |
|--|---------------|
| | REVISION |
| | 1 10-16-18 |
| | PV-306 |
| STANDARD ROAD PLAN | SHEET 3 of 4 |
| <small>REVISIONS: Modified x dimension in DIAGRAMMATIC PROFILES OF THE PAVEMENT EDGE LINES on SHEET 4.</small> | |
| <small>APPROVED BY DESIGN METHODS ENGINEER</small> | |
| SUPERELEVATION DETAILS EIGHT LANE ROADWAY CLOSED MEDIAN | |

| TABLE OF OFFSETS AND DROPS FOR LEFT ROADWAY | | | | | | | |
|---|--------------|-------|-------|------|------|------|-------|
| Location of Cross Sections | | (A) | (B) | (C) | (D) | (E) | (F) |
| From Line A To Line B | Offset (Ft.) | * | * | * | * | * | * |
| | Slope (%) | s | s | s | s | s | (3) |
| | Drop (Ft.) | | | | | | |
| From Line B To Line C | Offset (Ft.) | 12 | 12 | 12 | 12 | 12 | 12 |
| | Slope (%) | 2.5 | 2.5 | 2.5 | 2.5 | 2.5 | e |
| | Drop (Ft.) | 0.30 | 0.30 | 0.30 | 0.30 | 0.30 | 12(e) |
| From Line C To Line D | Offset (Ft.) | 12 | 12 | 12 | 12 | 12 | 12 |
| | Slope (%) | 2.0 | 2.0 | 2.0 | 2.0 | 2.5 | e |
| | Drop (Ft.) | 0.24 | 0.24 | 0.24 | 0.24 | 0.30 | 12(e) |
| From Line D To Line E | Offset (Ft.) | 12 | 12 | 12 | 12 | 12 | 12 |
| | Slope (%) | -2.0 | -2.0 | 0.0 | 2.0 | 2.5 | e |
| | Drop (Ft.) | -0.24 | -0.24 | 0.0 | 0.24 | 0.30 | 12(e) |
| From Line E To Line F | Offset (Ft.) | 12 | 12 | 12 | 12 | 12 | 12 |
| | Slope (%) | -2.5 | -2.0 | 0.0 | 2.0 | 2.5 | e |
| | Drop (Ft.) | -0.30 | -0.24 | 0.0 | 0.24 | 0.30 | 12(e) |

* Refer to plan details for shoulder width



DIAGRAMMATIC PROFILES OF THE PAVEMENT EDGE LINES

| TABLE OF OFFSETS AND DROPS FOR RIGHT ROADWAY | | | | | | | |
|--|--------------|-------|-------|-------|-------|-------|--------|
| Location of Cross Sections | | (A) | (B) | (C) | (D) | (E) | (F) |
| From Line A To Line B | Offset (Ft.) | * | * | * | * | * | * |
| | Slope (%) | s | s | s | s | s | (2) |
| | Drop (Ft.) | | | | | | |
| From Line B To Line C | Offset (Ft.) | 12 | 12 | 12 | 12 | 12 | 12 |
| | Slope (%) | 2.5 | 2.0 | 0.0 | -2.0 | -2.5 | -e |
| | Drop (Ft.) | 0.30 | 0.24 | 0.0 | -0.24 | -0.30 | -12(e) |
| From Line C To Line D | Offset (Ft.) | 12 | 12 | 12 | 12 | 12 | 12 |
| | Slope (%) | 2.0 | 2.0 | 0.0 | -2.0 | -2.5 | -e |
| | Drop (Ft.) | 0.24 | 0.24 | 0.0 | -0.24 | -0.30 | -12(e) |
| From Line D To Line E | Offset (Ft.) | 12 | 12 | 12 | 12 | 12 | 12 |
| | Slope (%) | -2.0 | -2.0 | -2.0 | -2.0 | -2.5 | -e |
| | Drop (Ft.) | -0.24 | -0.24 | -0.24 | -0.24 | -0.30 | -12(e) |
| From Line E To Line F | Offset (Ft.) | 12 | 12 | 12 | 12 | 12 | 12 |
| | Slope (%) | -2.5 | -2.5 | -2.5 | -2.5 | -2.5 | -e |
| | Drop (Ft.) | -0.30 | -0.30 | -0.30 | -0.30 | -0.30 | -12(e) |

* Refer to plan details for shoulder width

| | |
|--|------------|
| | REVISION |
| | 1 10-16-18 |
| STANDARD ROAD PLAN | PV-306 |
| SHEET 4 of 4 | |
| <small>REVISIONS: Modified x dimension in DIAGRAMMATIC PROFILES OF THE PAVEMENT EDGE LINES on SHEET 4.</small> | |
| <small>APPROVED BY DESIGN METHODS ENGINEER</small> | |
| SUPERELEVATION DETAILS EIGHT LANE ROADWAY CLOSED MEDIAN | |