



SPEED LIMIT (mph)	D	E	M	T
45 - 50	45'	300'	630'	100'
55 - 60	55'	400'	770'	100'
65 - 70	65'	500'	910'	100'

LEGEND

- Traffic Sign
- Drum
- 42" Channelizer
- Arrow Board
- Temporary Crash Cushion
- Work Area
- Direction of Traffic

When the Average Daily Traffic (ADT) exceeds 20,000 vehicles per day or when a traffic queue extends beyond the advanced signing, place RIGHT LANE CLOSED 4 MILES and RIGHT LANE CLOSED 2 MILES signs (W20-5) on both sides of the roadway 4 miles and 2 miles in advance of the lane closure, respectively.

Place Concrete Barrier Markers at 10 ft C/C on bridge rail.

- ① For roadways with a posted speed limit of 60 mph or greater before road work: Place SPEED LIMIT AHEAD sign and SPEED LIMIT 55 sign prior to the lane closure as shown. Place SPEED LIMIT 65 or 70 beyond the work area as shown.
- ② Refer to SI-881 for sign details.
- ③ For lanes closed to traffic, place two drums every 1000 feet. For full depth excavations in a closed lane, place two drums in front of each location. Additional drums need not be placed for full depth excavations spaced closer than 150 feet.

Possible Contract Items:
 Painted Symbols and Legends
 Pavement Marking Items
 Pavement Markings Removed
 Symbols and Legends Removed
 Temporary Barrier Rail
 Temporary Crash Cushions

Possible Tabulations:
 108-22
 108-29
 108-30
 108-33

 STANDARD ROAD PLAN	REVISION 15 04-16-19
	TC-421
	SHEET 1 of 1
REVISIONS: Removed Interim from the standard. Added circle note 3 and drums in the work area.	
 <small>APPROVED BY DESIGN METHODS ENGINEER</small>	
LANE CLOSURE WITH TBR	