

REVISED 05-13 -- THE GENERAL NOTES AND SPECIFICATIONS MOVED TO STANDARD SHEET H44-01A-07. SRL NOTATION ADDED.

INDEX FOR H44-07 STANDARDS:

H44-01-07 INDEX SHEET
H44-01A-07 GENERAL NOTES
H44-02-07 GENERAL INFORMATION
H44-03-07 SUPERSTRUCTURE DETAILS
H44-04-07 SUPERSTRUCTURE DETAILS-MISC.
H44-05-07 ABUTMENT DETAILS FOR 0° SKEW, A & B BEAMS
H44-06-07 ABUTMENT DETAILS FOR 0° SKEW, C BEAMS
H44-07-07 LONGITUDINAL SECTION FOR 0° SKEW, A & B BEAMS
H44-08-07 LONGITUDINAL SECTION FOR 0° SKEW, C BEAMS
H44-09-07 SUPERSTRUCTURE DETAILS FOR 0° SKEW
H44-10-07 DECK & ABUTMENT REINF. FOR 0° SKEW
H44-11-07 ABUTMENT DETAILS FOR 15° SKEW, A & B BEAMS
H44-12-07 ABUTMENT DETAILS FOR 15° SKEW, C BEAMS
H44-13-07 LONGITUDINAL SECTION FOR 15° SKEW, A & B BEAMS
H44-14-07 LONGITUDINAL SECTION FOR 15° SKEW, C BEAMS
H44-15-07 SUPERSTRUCTURE DETAILS FOR 15° SKEW
H44-16-07 DECK & ABUTMENT REINF. FOR 15° SKEW
H44-17-07 ADDITIONAL QUANTITIES FOR 15° SKEW
H44-18-07 ABUTMENT DETAILS FOR 30° SKEW, A & B BEAMS
H44-19-07 ABUTMENT DETAILS FOR 30° SKEW, C BEAMS
H44-20-07 LONGITUDINAL SECTION FOR 30° SKEW, A & B BEAMS
H44-21-07 LONGITUDINAL SECTION FOR 30° SKEW, C BEAMS
H44-22-07 SUPERSTRUCTURE DETAILS FOR 30° SKEW
H44-23-07 DECK & ABUTMENT REINF. FOR 30° SKEW
H44-24-07 ADDITIONAL QUANTITIES FOR 30° SKEW
H44-25-07 A BEAM DETAILS
H44-26-07 A BEAM DETAILS
H44-27-07 B BEAM DETAILS
H44-28-07 B BEAM DETAILS
H44-29-07 C BEAM DETAILS
H44-30-07 C BEAM DETAILS
H44-31-07 INTERMEDIATE STEEL DIAPHRAGMS
H44-32-07 BARRIER RAIL DETAILS 1 OF 3
H44-33-07 BARRIER RAIL DETAILS 2 OF 3
H44-34-07 BARRIER RAIL DETAILS 3 OF 3
H44-35-07 OPEN RAIL DETAILS 1 OF 2
H44-36-07 OPEN RAIL DETAILS 2 OF 2
H44-37-07 PIER BEARING DETAILS

INDEX FOR H44-07 STANDARDS (CONT'D.):

H44-38-07 PILE BENT PIERS FOR 0° SKEW
H44-39-07 PILE BENT PIERS FOR 0° SKEW
H44-40-07 PILE BENT PIERS HP14 PILES FOR 0° SKEW
H44-41-07 PILE BENT PIERS HP14 PILES FOR 0° SKEW
H44-42-07 PILE BENT PIERS FOR 15° SKEW
H44-43-07 PILE BENT PIERS FOR 15° SKEW
H44-44-07 PILE BENT PIERS HP14 PILES FOR 15° SKEW
H44-45-07 PILE BENT PIERS HP14 PILES FOR 15° SKEW
H44-46-07 PILE BENT PIERS FOR 30° SKEW
H44-47-07 PILE BENT PIERS FOR 30° SKEW
H44-48-07 PILE BENT PIERS HP14 PILES FOR 30° SKEW
H44-49-07 PILE BENT PIERS HP14 PILES FOR 30° SKEW
H44-50-07 TEE PIER CAP AND COLUMN, 0° SKEW
H44-51-07 TEE PIER CAP AND COLUMN, 0° SKEW
H44-52-07 TEE PIER-HP10x57 SRL-1 PILE FOOTINGS 0° SKEW, H=16' TO 24'
H44-53-07 TEE PIER-HP10x57 SRL-1 PILE FOOTINGS 0° SKEW, H=25' TO 40'
H44-54-07 TEE PIER-HP10x57 SRL-2 PILE FOOTINGS 0° SKEW, H=16' TO 24'
H44-55-07 TEE PIER-HP10x57 SRL-2 PILE FOOTINGS 0° SKEW, H=25' TO 40'
H44-56-07 TEE PIER-SPREAD FOOTINGS, 0° SKEW, H=16' TO 24'
H44-57-07 TEE PIER-SPREAD FOOTINGS, 0° SKEW, H=25' TO 40'
H44-58-07 TEE PIER CAP AND COLUMN, 15° SKEW
H44-59-07 TEE PIER CAP AND COLUMN, 15° SKEW
H44-60-07 TEE PIER-HP10x57 SRL-1 PILE FOOTINGS, 15° SKEW, H=16' TO 24'
H44-61-07 TEE PIER-HP10x57 SRL-1 PILE FOOTINGS, 15° SKEW, H=25' TO 40'
H44-62-07 TEE PIER-HP10x57 SRL-2 PILE FOOTINGS, 15° SKEW, H=16' TO 24'
H44-63-07 TEE PIER-HP10x57 SRL-2 PILE FOOTINGS, 15° SKEW, H=25' TO 40'
H44-64-07 TEE PIER-SPREAD FOOTINGS, 15° SKEW, H=16' TO 24'
H44-65-07 TEE PIER-SPREAD FOOTINGS, 15° SKEW, H=25' TO 40'
H44-66-07 TEE PIER CAP AND COLUMN, 30° SKEW
H44-67-07 TEE PIER CAP AND COLUMN, 30° SKEW
H44-68-07 TEE PIER-HP10x57 SRL-1 PILE FOOTINGS, 30° SKEW, H=16' TO 24'
H44-69-07 TEE PIER-HP10x57 SRL-1 PILE FOOTINGS, 30° SKEW, H=25' TO 40'
H44-70-07 TEE PIER-HP10x57 SRL-2 PILE FOOTINGS, 30° SKEW, H=16' TO 24'
H44-71-07 TEE PIER-HP10x57 SRL-2 PILE FOOTINGS, 30° SKEW, H=25' TO 40'
H44-72-07 TEE PIER-SPREAD FOOTINGS, 30° SKEW, H=16' TO 24'
H44-73-07 TEE PIER-SPREAD FOOTINGS, 30° SKEW, H=25' TO 40'
H44-74-07 SUBDRAIN DETAILS
H44-75-07 WING ARMORING DETAILS, A & B BEAMS
H44-76-07 WING ARMORING DETAILS, C BEAMS
H44-77-07 ABUTMENT BACKFILL DETAIL, A & B BEAMS - 0° SKEW
H44-78-07 ABUTMENT BACKFILL DETAIL, A & B BEAMS - SKEWED
H44-79-07 ABUTMENT BACKFILL DETAIL, C BEAMS - 0° SKEW
H44-80-07 ABUTMENT BACKFILL DETAIL, C BEAMS - SKEWED

STRUCTURAL RESISTANCE LEVEL-1 (SRL-1) REPLACES THE 50 TON STEEL PILE DESIGNATION.

STRUCTURAL RESISTANCE LEVEL 2 (SRL-2) REPLACES THE 75 TON STEEL PILE DESIGNATION.

FOR MORE INFORMATION ON STRUCTURAL RESISTANCE LEVELS (SRL-1 & SRL-2), SEE THE BRIDGE DESIGN MANUAL, LOCATED ON THE IOWA DEPARTMENT OF TRANSPORTATIONS, OFFICE OF BRIDGES AND STRUCTURES, WEB SITE.

LATEST REVISION DATE 05-13	 APPROVED BY BRIDGE ENGINEER	 Iowa Department of Transportation Highway Division
		STANDARD DESIGN - 44' ROADWAY, THREE SPAN BRIDGE PRETENSIONED PRESTRESSED CONCRETE BEAM BRIDGES MARCH, 2007
		INDEX SHEET
		H44-01-07