



When a pavement edge drop-off exists, install a SHOULDER DROP-OFF sign.

No pavement edge drop-offs greater than pavement depth will be allowed during non-working hours.

Shoulder edge drop-offs shall be mitigated according to Article 1107.08.K2 of the Standard Specifications.

For work lasting less than one hour, refer to TC-1.

Possible Contract Item:
Traffic Control

LEGEND

- † Traffic Sign
- 42" Channelizer
- Work Area
- ← Direction of Traffic

| SPEED LIMIT (mph) | A | B | C ^② | T |
|-------------------|-------|------|-------------------|------|
| 40 or less | 500' | 250' | 40' | 100' |
| 45 - 50 | 700' | 350' | 80' ^① | 200' |
| 55 - 60 | 1500' | 500' | 100' ^① | 200' |
| 65 - 70 | 1500' | 500' | 100' ^① | 230' |

^① When the length of a pavement edge drop-off is 1000 feet or less, the temporary fillet requirement of Article 1107.08 of the Standard Specifications does not apply. Reduce channelizer spacing to 40 feet.

^② For work areas less than 200 feet long, use channelizers spaced at 20 foot centers or use a vehicle with an amber revolving light or amber strobe light.

| | |
|--|--------------|
| | REVISION |
| | 9 10-19-21 |
| STANDARD ROAD PLAN | TC-402 |
| REVISIONS: Updated specification reference | SHEET 1 of 1 |
| <small>APPROVED BY DESIGN METHODS ENGINEER</small> | |
| WORK WITHIN 15 FT OF TRAVELED WAY | |