



Where there is a lane line drop-off or rise, do not allow traffic to cross over the drop-off or rise, except for ramp locations where a BUMP (W8-1) sign is placed.

Lane line drop-offs greater than a nominal 4 inches are not allowed during non-working hours.

- ① Refer to [SI-881](#) for sign details.
- ② For roadways with a posted speed limit of 60 mph or greater before road work:
  - Place SPEED LIMIT 55 signs prior to the lane closure as shown.
  - When the length of closure is greater than 1 mile, install SPEED LIMIT 55 signs in the closed lane at 1-mile intervals.
  - Remove or cover all existing signs that conflict with 55 mph speed limit while 55 mph speed limit is in effect.
  - For traffic control zones lasting more than 4 hours, place a Speed Feedback Sign at the end of the merge taper.
- ③ For lanes closed to traffic, place two drums every 1000 feet. For full depth excavations in a closed lane, place two drums in front of each location. Additional drums need not be placed for full depth excavations spaced closer than 150 feet.

Possible Contract Item:  
Traffic Control

**LEGEND**

- Direction Of Traffic
- Traffic Sign
- Drum
- 42" Channelizer
- Speed Feedback Sign
- Arrow Board
- Work Area

SPEED LIMIT (mph)	A	C	D	E	M	T	A1
35 or less	250'	40'	35'	0'-200'	245'	50'	250'
40	500'	80'	40'	0'-300'	320'	50'	500'
45	700'	80'	45'	0'-400'	630'	100'	700'
50	700'	80'	45'	400'	630'	100'	700'
55 - 60	1000'	100'	55'	600'	770'	100'	2000'
65 - 70	1000'	100'	65'	700'	910'	100'	2000'

 <b>STANDARD ROAD PLAN</b>	REVISION	
	14	04-19-22
<b>TC-422</b>		
SHEET 1 of 1		
REVISIONS: Removed note about traffic over 20,000 ADT.		
<i>Steve Miller</i> APPROVED BY DESIGN METHODS ENGINEER		
<b>CLOSURE OF TWO ADJACENT LANES ON DIVIDED HIGHWAY</b>		