






For joint details, refer to PV-101.




 Iowa Department of Transportation	REVISION	
	2	04-19-11
STANDARD ROAD PLAN	SW-541	
SHEET 1 of 2		
REVISIONS: Updated references to renamed standards.		
 APPROVED BY DESIGN METHODS ENGINEER		
OPEN-THROAT CURB INTAKE UNDER PAVEMENT		



- ① 39 inches when attaching the SW-542 extension unit.
- ② Additional keyed construction joint when attaching the SW-542 extension unit.
- ③ Modify dimensions as required to accommodate other curb heights when specified.

REINFORCING BAR LIST					
Mark	Size	Location	Shape	Length	Spacing
a1	4	Base	—	5'-0"	14"
a2	4	Base	—	5'-0"	14"
b1	4	Wall	—	3'-0"	14"
c1	4	Top	┌	2'-8"	14"
c2	4	Top	—	5'-0"	See Detail
c3	4	Top	—	5'-0"	See Detail
c4	4	Top	—	3'-4"	See Detail

 Iowa Department of Transportation	REVISION	
	2	04-19-11
STANDARD ROAD PLAN	SW-541	
SHEET 2 of 2		
REVISIONS: Updated references to renamed standards.		
 APPROVED BY DESIGN METHODS ENGINEER		
OPEN-THROAT CURB INTAKE UNDER PAVEMENT		