

-6" min.

SECTION B-B

3" Clear

5a1 Base

5a2 Base

8b1

5a1 Base

5a2 Base

8b1

5a1

5a2

8b1 Base

5a1

5a2 Base

8b1

Base

Base

Base

Base

Base

15"

21"

24"

2

2

2

2

9

2

2

11

2

2

13

12'-10"

2'-11"

3'-1"

15'-0"

3'-2"

3'-4"

17'-2"

3'-5"

3'-7"

19'-4"

3'-8"

3'-10"

25.7

5.9

21.6

30.0

6.4

30.0

34.4

6.9

39.5

38.7

7.4

49.9

26.8

6.2

57.7

31.3

6.7

80.1

35.9

7.2

105.5

40.4

7.7

133.2

148.6

181.3

See Detail

See Detail

12"

Reinforcing steel used in construction of "Beveled Pipe and Guard" is deformed bars meeting the requirements of Article 4151.03. All steel bars to be hot-dip galvanized in accordance with ASTM A123 specifications.

Use Class 'C' Concrete in the construction of Beveled Pipe and Guard.

Cut the pipe to fit the foreslope. Cut slots into the pipe for placement of the No. 8 bars. After the foreslope has been placed, fit the No. 8 bars into the slots cut in the pipe so they will be in proper position when the concrete collar is poured.

Price bid for "Beveled Pipe and Guard," each, is full compensation for furnishing all materials and constructing the Beveled Pipe and Guard.

Special Note:

A silt fence ditch check will be required immediately upstream from the inlet. Refer to EC-201 for construction

Possible Contract Item: **Beveled Pipe and Guard**

Possible Tabulations: 104-3 112-8



Deanna Maifuld PROVED BY DESIGN METHODS ENGINEE

2 10-19-10

RF-27

SHEET 1 of 1

BEVELED PIPE AND GUARD