

Sampling & Testing Guide-Minimum Frequency

October 17, 2006
Supersedes October 18, 2005

SOIL AGGREGATE SUBBASE
Section 2110

Matls. IM 204
Appendix B

MATERIAL OR CONSTRUCTION ITEM	TESTS	METHOD OF ACCEPTANCE & RELATED IMs	QUALITY CONTROL					INDEPENDENT ASSURANCE & VERIFICATION S&T					REMARKS	
			SAMPLE BY	FREQ.	SAMPLE SIZE	TEST BY	REPORT	S&T TYPE	SAMPLE BY	FREQ.	SAMPLE SIZE	TEST BY		REPORT
SOURCE INSPECTION														
Granular Surfacing Material (4120)		AS 209												
GRADE INSPECTION														
Mixed Materials (2110)	Density (Proctor)	309	RCE	2/mile (min. 2/proj.)	5000 gm	RCE	Field Book							Change of Soil type requires additional Proctors
Uncompacted Mixture	Pulverization Moisture	2" Sieve Visual	RCE	2/mile		RCE	Field Book							
Compacted Mixture (2110)	Density Thickness Width	311, 312, 334 337						V	RCE	2/mile		RCE	Field Book	
Finished Subbase	Cross Section	Stringline						V	RCE	10/mile		RCE	Field Book	Template for secondary park & institutional roads
AS-Approved Source ASD-Approved Shop Drawing S&T-Sampling & Testing			Cert A-Type A Certification Cert C-Type C Certification Cert D-Type D Certification				RCE-Resident Construction Engineer/Project Engineer DME-District Materials Engineer CTRL-Central Materials Office CONTR-Contractor				IA-Independent Assurance V-Verification			