Matls. IM 451.03B Appendix D

****THIS IS A NEW APPENDIX. - PLEASE READ CAREFULLY.****

EPOXY COATED STEEL REINFORCEMENT APPROVED SUPPLIERS / DISTRIBUTORS WAREHOUSE MONITOR INSPECTION FORM

Supplier / Distributor Name	
Location	
Contact Person	
Steel Sources	
(must be on the approved list IM 451 and Appendices)	
Current / up-to-date written Q.C. Procedures in place	
Date of last in-house review / update	
Material stored above ground on proper cribbing or timber	
Storage indoor / outdoor	
Heat number on tags are clearly legible	
Coater name / powder source	
Bandles properly banded with suitable padding to prevent damage to the coating	
If stacked, is there adequate padding / timber between bundles	
Bar lengths properly supported to prevent sagging	
Bar / Bandles properly moved – no dragging or dropping	
Weather protection – if stored outside (greater than two months) shall be protected from sunlight, salt spray, and weather exposure. The coated bars shall be covered with non-transparent material or other suitable opaque protective materials and provisions shall be made for adequate ventilation to minimize condensation.	
Date of coated bars placed outdoors should be recorded on an identification tag	

Discolored (weathered) bars should be rejected
Records keeping – Certified Mill Test Reports / Coater / Powder sources
Special areas designated for state certified steel reinforcement
All coated bar reinforcements are from approved source and are of domestic origin