

2	10/17/06	
REV.	DATE	BY
DATE: 01-01-98		
JOINTS (LONGITUDINAL CONTRACTION)		
SEE DETAIL "B" PLAIN JOINT FOR ABUTTING PAVEMENT SLABS 'B' #4 BAR FOR BT-1 JOINT #5 BAR FOR BT-2 JOINT ABUTTING PAVEMENT JOINT - RIGID TIE WHERE T IS LESS THAN 8" 'BT-1' ⑤ 36" LONG AT 30" CENTERS WHERE T IS 8" OR MORE 'BT-2' ⑤ 36" LONG AT 30" CENTERS 3/4" DIA. HOLE FOR BT-3 & BT-4 JOINT. 5/8" DIA. HOLE FOR BT-5 JOINT. 9" MIN. 15" MIN. ABUTTING PAVEMENT JOINT - RIGID TIE WHERE T IS 8" OR MORE 'BT-3' ⑤ 24" LONG AT 30" CENTERS 'BT-4' ⑤ 36" LONG AT 15" CENTERS WHERE T IS LESS THAN 8" 'BT-5' ⑤ 24" LONG AT 30" CENTERS SEE DETAIL "C" SEE DETAIL "C" KEYED JOINT FOR ADJACENT SLABS WHERE T IS 8" OR MORE SEE DETAIL "C" SEE DETAIL "C" #4 BARS @ 30" CENTERS. (CONTINUOUS ACROSS JOINT OR LAP A MIN. OF 15") 'KS' LONGITUDINAL JOINT FOR REINFORCED PAVEMENT SEE DETAIL "C" SEE DETAIL "C" #4 BAR FOR KT-1 JOINT #5 BAR FOR KT-2 & KT-3 JOINT ABUTTING PAVEMENT JOINT - KEYWAY TIE WHERE T IS LESS THAN 8" 'KT-1' ①⑤ 30" LONG AT 30" CENTERS WHERE T IS 8" OR MORE 'KT-2' ①⑤ 30" LONG AT 30" CENTERS 'KT-3' ①⑤ 30" LONG AT 15" CENTERS SEE DETAIL "A" SEE DETAIL "A" #4 BAR FOR L-1 JOINT #5 BAR FOR L-2 & L-3 JOINT 'L-1', 'L-2', & 'L-3' WHERE T IS LESS THAN 8" 'L-1' ⑤ 36" LONG AT 30" CENTERS WHERE T IS 8" OR MORE 'L-2' ⑤ 36" LONG AT 30" CENTERS 'L-3' ⑤ 36" LONG AT 15" CENTERS		
FIGURE: 7010.4B		
SHEET 1 OF 2		

