

REVISED 04-13 - THE GENERAL NOTES AND SPECIFICATIONS MOVED TO STANDARD SHEET H30-01A-06. SRL NOTATION ADDED.

### INDEX FOR H30-06 STANDARDS:

H30-01-06	INDEX SHEET
H30-01A-06	GENERAL NOTES
H30-02-06	GENERAL INFORMATION
H30-03-06	SUPERSTRUCTURE DETAILS
H30-04-06	SUPERSTRUCTURE DETAILS-MISC.
H30-05-06	ABUTMENT DETAILS FOR 0° SKEW, A & B BEAMS
H30-06-06	ABUTMENT DETAILS FOR 0° SKEW, C BEAMS
H30-07-06	LONGITUDINAL SECTION FOR 0° SKEW, A & B BEAMS
H30-08-06	LONGITUDINAL SECTION FOR 0° SKEW, C BEAMS
H30-09-06	SUPERSTRUCTURE DETAILS FOR 0° SKEW
H30-10-06	DECK & ABUTMENT REINF. FOR 0° SKEW
H30-11-06	ABUTMENT DETAILS FOR 15° SKEW, A & B BEAMS
H30-12-06	ABUTMENT DETAILS FOR 15° SKEW, C BEAMS
H30-13-06	LONGITUDINAL SECTION FOR 15° SKEW, A & B BEAMS
H30-14-06	LONGITUDINAL SECTION FOR 15° SKEW, C BEAMS
H30-15-06	SUPERSTRUCTURE DETAILS FOR 15° SKEW
H30-16-06	DECK & ABUTMENT REINF. FOR 15° SKEW
H30-17-06	ADDITIONAL QUANTITIES FOR 15° SKEW
H30-18-06	ABUTMENT DETAILS FOR 30° SKEW, A & B BEAMS
H30-19-06	ABUTMENT DETAILS FOR 30° SKEW, C BEAMS
H30-20-06	LONGITUDINAL SECTION FOR 30° SKEW, A & B BEAMS
H30-21-06	LONGITUDINAL SECTION FOR 30° SKEW, C BEAMS
H30-22-06	SUPERSTRUCTURE DETAILS FOR 30° SKEW
H30-23-06	DECK & ABUTMENT REINF. FOR 30° SKEW
H30-24-06	ADDITIONAL QUANTITIES FOR 30° SKEW
H30-25-06	ABUTMENT DETAILS FOR 45° SKEW, A & B BEAMS
H30-26-06	ABUTMENT DETAILS FOR 45° SKEW, C BEAMS
H30-27-06	LONGITUDINAL SECTION FOR 45° SKEW, A & B BEAMS
H30-28-06	LONGITUDINAL SECTION FOR 45° SKEW, C BEAMS
H30-29-06	SUPERSTRUCTURE DETAILS FOR 45° SKEW
H30-30-06	DECK & ABUTMENT REINF. FOR 45° SKEW
H30-31-06	ADDITIONAL QUANTITIES FOR 45° SKEW
H30-32-06	A BEAM DETAILS
H30-33-06	A BEAM DETAILS
H30-34-06	B BEAM DETAILS
H30-35-06	B BEAM DETAILS
H30-36-06	C BEAM DETAILS
H30-37-06	C BEAM DETAILS
H30-38-06	INTERMEDIATE STEEL DIAPHRAGMS
H30-39-06	BARRIER RAIL DETAILS 1 OF 3
H30-40-06	BARRIER RAIL DETAILS 2 OF 3
H30-41-06	BARRIER RAIL DETAILS 3 OF 3
H30-42-06	OPEN RAIL DETAILS 1 OF 2
H30-43-06	OPEN RAIL DETAILS 2 OF 2
H30-44-06	PIER BEARING DETAILS



### INDEX FOR H30-06 STANDARDS (CONT'D.):

H30-45-06	PILE BENT PIERS FOR 0° SKEW
H30-46-06	PILE BENT PIERS FOR 0° SKEW
H30-47-06	PILE BENT PIERS-HP14 PILES FOR 0° SKEW
H30-48-06	PILE BENT PIERS FOR 15° SKEW
H30-49-06	PILE BENT PIERS FOR 15° SKEW
H30-50-06	PILE BENT PIERS HP14 PILES FOR 15° SKEW
H30-51-06	PILE BENT PIERS FOR 30° SKEW
H30-52-06	PILE BENT PIERS FOR 30° SKEW
H30-53-06	PILE BENT PIERS HP14 PILES FOR 30° SKEW
H30-54-06	PILE BENT PIERS FOR 45° SKEW
H30-55-06	PILE BENT PIERS FOR 45° SKEW
H30-56-06	PILE BENT PIERS HP14 PILES FOR 45° SKEW
H30-57-06	TEE PIER CAP AND COLUMN, 0° SKEW
H30-58-06	TEE PIER-HP10x57 SRL-1 PILE FOOTINGS 0° SKEW, H=16' TO 24'
H30-59-06	TEE PIER-HP10x57 SRL-1 PILE FOOTINGS 0° SKEW, H=25' TO 40'
H30-60-06	TEE PIER-HP10x57 SRL-2 PILE FOOTINGS 0° SKEW, H=16' TO 24'
H30-61-06	TEE PIER-HP10x57 SRL-2 PILE FOOTINGS 0° SKEW, H=25' TO 40'
H30-62-06	TEE PIER-SPREAD FOOTINGS, 0° SKEW, H=16' TO 24'
H30-63-06	TEE PIER-SPREAD FOOTINGS, 0° SKEW, H=25' TO 40'
H30-64-06	TEE PIER CAP AND COLUMN, 15° SKEW
H30-65-06	TEE PIER-HP10x57 SRL-1 PILE FOOTINGS, 15° SKEW, H=16' TO 24'
H30-66-06	TEE PIER-HP10x57 SRL-1 PILE FOOTINGS, 15° SKEW, H=25' TO 40'
H30-67-06	TEE PIER-HP10x57 SRL-2 PILE FOOTINGS, 15° SKEW, H=16' TO 24'
H30-68-06	TEE PIER-HP10x57 SRL-2 PILE FOOTINGS, 15° SKEW, H=25' TO 40'
H30-69-06	TEE PIER-SPREAD FOOTINGS, 15° SKEW, H=16' TO 24'
H30-70-06	TEE PIER-SPREAD FOOTINGS, 15° SKEW, H=25' TO 40'
H30-71-06	TEE PIER CAP AND COLUMN, 30° SKEW
H30-72-06	TEE PIER-HP10x57 SRL-1 PILE FOOTINGS, 30° SKEW, H=16' TO 24'
H30-73-06	TEE PIER-HP10x57 SRL-1 PILE FOOTINGS, 30° SKEW, H=25' TO 40'
H30-74-06	TEE PIER-HP10x57 SRL-2 PILE FOOTINGS, 30° SKEW, H=16' TO 24'
H30-75-06	TEE PIER-HP10x57 SRL-2 PILE FOOTINGS, 30° SKEW, H=25' TO 40'
H30-76-06	TEE PIER-SPREAD FOOTINGS, 30° SKEW, H=16' TO 24'
H30-77-06	TEE PIER-SPREAD FOOTINGS, 30° SKEW, H=25' TO 40'
H30-78-06	TEE PIER CAP AND COLUMN, 45° SKEW
H30-79-06	TEE PIER-HP10x57 SRL-1 PILE FOOTINGS, 45° SKEW, H=16' TO 24'
H30-80-06	TEE PIER-HP10x57 SRL-1 PILE FOOTINGS, 45° SKEW, H=25' TO 40'
H30-81-06	TEE PIER-HP10x57 SRL-2 PILE FOOTINGS, 45° SKEW, H=16' TO 24'
H30-82-06	TEE PIER-HP10x57 SRL-2 PILE FOOTINGS, 45° SKEW, H=25' TO 40'
H30-83-06	TEE PIER-SPREAD FOOTINGS, 45° SKEW, H=16' TO 24'
H30-84-06	TEE PIER-SPREAD FOOTINGS, 45° SKEW, H=25' TO 40'
H30-85-06	SUBDRAIN DETAILS
H30-86-06	WING ARMORING DETAILS, A & B BEAMS
H30-87-06	WING ARMORING DETAILS, C BEAMS
H30-88-06	ABUTMENT BACKFILL DETAIL, A & B BEAMS - 0° SKEW
H30-89-06	ABUTMENT BACKFILL DETAIL, A & B BEAMS - SKEWED
H30-90-06	ABUTMENT BACKFILL DETAIL, C BEAMS - 0° SKEW
H30-91-06	ABUTMENT BACKFILL DETAIL, C BEAMS - SKEWED

STRUCTURAL RESISTANCE LEVEL-1 (SRL-1) REPLACES THE 50 TON STEEL PILE DESIGNATION.

STRUCTURAL RESISTANCE LEVEL-2 (SRL-2) REPLACES THE 75 TON STEEL PILE DESIGNATION.

FOR MORE INFORMATION ON STRUCTURAL RESISTANCE LEVELS (SRL-1 & SRL-2), SEE THE BRIDGE DESIGN MANUAL, LOCATED ON THE IOWA DEPARTMENT OF TRANSPORTATIONS, OFFICE OF BRIDGES AND STRUCTURES, WEBSITE.

04-13 LATEST REVISION DATE	 APPROVED BY BRIDGE ENGINEER	 <b>Iowa Department of Transportation</b> Highway Division STANDARD DESIGN - 30' ROADWAY, THREE SPAN BRIDGES <b>PRETENSIONED PRESTRESSED CONCRETE BEAM BRIDGES</b> DECEMBER, 2006
INDEX SHEET		H30-01-06