


EPOXY COATED REINFORCING BAR LIST

			BRIDGE LENGTH																													
ONE SUPERSTRUCTURE AND TWO ABUTMENTS			160'-0		180'-0		200'-0		220'-0		240'-0		260'-0		280'-0		300'-0		320'-0		340'-0											
BAR	LOCATION	SHAPE	NO.	LENGTH	WEIGHT	NO.	LENGTH	WEIGHT	NO.	LENGTH	WEIGHT	NO.	LENGTH	WEIGHT	NO.	LENGTH	WEIGHT	NO.	LENGTH	WEIGHT	NO.	LENGTH	WEIGHT									
6a1	SLAB TRANSVERSE, TOP & BOTTOM		355	42'-10	22,840	403	42'-10	25,928	451	42'-10	29,016	499	42'-10	32,104	547	42'-10	35,192	595	42'-10	38,280	643	42'-10	41,368	691	42'-10	44,456	739	42'-10	47,545	787	42'-10	50,633
6a2	SLAB TRANSVERSE, TOP-ENDS		34	VARIES	1116	34	VARIES	1116	34	VARIES	1116	34	VARIES	1116	34	VARIES	1116	34	VARIES	1116	34	VARIES	1116	34	VARIES	1116	34	VARIES	1116	34	VARIES	1116
6a3	SLAB TRANSVERSE, BOTTOM-ENDS		36	VARIES	1181	36	VARIES	1181	36	VARIES	1181	36	VARIES	1181	36	VARIES	1181	36	VARIES	1181	36	VARIES	1181	36	VARIES	1181	36	VARIES	1181	36	VARIES	1181
6b1	SLAB LONGITUDINAL TOP & BOTTOM		485	34'-6	25,133	485	38'-6	28,047	582	35'-10	31,325	582	39'-2	34,239	679	36'-9	37,480	679	39'-8	40,455	776	37'-6	43,709	776	40'-0	46,623	873	38'-0	49,828	970	36'-6	53,179
5d2	ABUTMENT DIAPHRAGM, LONGITUDINAL		16	22'-5	375	16	22'-5	375	16	22'-5	375	16	22'-5	375	16	22'-5	375	16	22'-5	375	16	22'-5	375	16	22'-5	375	16	22'-5	375	16	22'-5	375
5d5	ABUTMENT DIAPHRAGM, LONGITUDINAL - END		16	5'-0	84	16	5'-0	84	16	5'-0	84	16	5'-0	84	16	5'-0	84	16	5'-0	84	16	5'-0	84	16	5'-0	84	16	5'-0	84	16	5'-0	84
5d6	ABUTMENT DIAPHRAGM, LONGITUDINAL - B.F.		16	23'-10	398	16	23'-10	398	16	23'-10	398	16	23'-10	398	16	23'-10	398	16	23'-10	398	16	23'-10	398	16	23'-10	398	16	23'-10	398	16	23'-10	398
5d7	PAVING NOTCH, LONGITUDINAL		8	23'-8	197	8	23'-8	197	8	23'-8	197	8	23'-8	197	8	23'-8	197	8	23'-8	197	8	23'-8	197	8	23'-8	197	8	23'-8	197	8	23'-8	197
5d8	ABUT. DIAPHRAGM WING EXT. LONGIT.		-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
5d9	ABUT. DIAPHRAGM WING EXT. LONGIT.		-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
8f1	ABUTMENT FOOTING LONGITUDINAL - B.F.		36	25'-1	2412	36	25'-1	2412	36	25'-1	2412	36	25'-1	2412	36	25'-1	2412	36	25'-1	2412	36	25'-1	2412	36	25'-1	2412	36	25'-1	2412	36	25'-1	2412
8f3	ABUTMENT EXTENSION LONGITUDINAL		-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
8f4	ABUTMENT EXTENSION LONGITUDINAL		-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
8f5	ABUTMENT EXTENSION LONGITUDINAL		-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
8g1	ABUTMENT VERTICAL - B.F.		136	6'-5	2331	136	6'-5	2331	136	6'-8	2421	136	6'-11	2512	136	6'-11	2512	136	7'-1	2573	136	7'-2	2603	136	7'-2	2603	136	7'-2	2603	136	7'-6	2724
8g3	ABUTMENT DIAPHRAGM VERTICAL - B.F.		62	15'-3	2525	62	15'-3	2525	62	15'-3	2525	62	15'-3	2525	62	15'-3	2525	62	15'-3	2525	62	15'-3	2525	62	15'-3	2525	62	15'-3	2525	62	15'-3	2525
6g4	ABUTMENT DIAPHRAGM WING EXT. VERT.		-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
5h1	WING HORIZONTAL BACK FACE		28	6'-8	195	28	6'-8	195	28	6'-8	195	28	6'-8	195	28	6'-8	195	28	6'-8	195	28	6'-8	195	28	6'-8	195	28	6'-8	195	28	6'-8	195
5h2	WING HORIZONTAL BACK FACE		56	4'-11	288	56	4'-11	288	56	4'-11	288	56	4'-11	288	56	4'-11	288	56	4'-11	288	56	4'-11	288	56	4'-11	288	56	4'-11	288	56	4'-11	288
5h3	WING HORIZONTAL TRAFFIC FACE		28	6'-9	198	28	6'-9	198	28	6'-9	198	28	6'-9	198	28	6'-9	198	28	6'-9	198	28	6'-9	198	28	6'-9	198	28	6'-9	198	28	6'-9	198
5h4	WING HORIZONTAL TRAFFIC FACE		-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
5j1	TOP OF SLAB, TRANSVERSE, AT RAIL		384	6'-3	2504	432	6'-3	2817	480	6'-3	3129	528	6'-3	3442	576	6'-3	3755	624	6'-3	4068	672	6'-3	4381	720	6'-3	4694	768	6'-3	5007	816	6'-3	5320
5k1	PAVING NOTCH, TRANSVERSE		64	4'-3	284	64	4'-3	284	64	4'-3	284	64	4'-3	284	64	4'-3	284	64	4'-3	284	64	4'-3	284	64	4'-3	284	64	4'-3	284	64	4'-3	284
5k2	PAVING NOTCH, TRANSVERSE		64	3'-5	229	64	3'-5	229	64	3'-5	229	64	3'-5	229	64	3'-5	229	64	3'-5	229	64	3'-5	229	64	3'-5	229	64	3'-5	229	64	3'-5	229
5p1	ABUTMENT HOOPS		140	10'-6	1534	140	10'-6	1534	140	10'-6	1534	128	10'-6	1402	128	10'-6	1402	128	10'-6	1402	144	10'-6	1578	144	10'-6	1578	144	10'-6	1578	144	10'-6	1578
5p2	ABUTMENT HOOPS AT ENDS		8	11'-0	92	8	11'-0	92	8	11'-0	92	8	11'-0	92	8	11'-0	92	8	11'-0	92	8	11'-0	92	8	11'-0	92	8	11'-0	92	8	11'-0	92
6p3	ABUTMENT BOTTOM AT PILES		32	6'-8	321	32	6'-8	321	32	6'-8	321	36	6'-8	361	36	6'-8	361	36	6'-8	361	40	6'-8	401	40	6'-8	401	40	6'-8	401	40	6'-8	401
5p4	ABUTMENT EXTENSION HOOPS		-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
5s1	WING, VERTICAL		64	5'-7	373	64	5'-7	373	64	5'-7	373	64	6'-2	412	64	6'-2	412	64	6'-2	412	64	6'-2	412	64	6'-2	412	64	6'-2	412	64	6'-11	462
4t1	UNDER BEAMS AT ABUTMENTS		12	4'-7	37	12	4'-7	37	12	4'-7	37	12	4'-7	37	12	4'-7	37	12	4'-7	37	12	4'-7	37	12	4'-7	37	12	4'-7	37	12	4'-7	37
4t2	ABUTMENT DIAPHRAGM, LONGITUDINAL F.F.		36	7'-6	181	36	7'-6	181	36	7'-6	181	36	7'-6	181	36	7'-6	181	36	7'-6	181	36	7'-6	181	36	7'-6	181	36	7'-6	181	36	7'-6	181
* PILE SPIRAL - NO. 2 BAR			16	38'-6	103	16	38'-6	103	16	38'-6	103	18	38'-6	116	18	38'-6	116	18	38'-6	116	20	38'-6	129	20	38'-6	129	20	38'-6	129	24	38'-6	155
* SPIRAL SPACER L ₄ x L ₄ x L ₄ x 0.70			48	1'-10	62	48	1'-10	62	48	1'-10	62	54	1'-10	70	54	1'-10	70	54	1'-10	70	60	1'-10	77	60	1'-10	77	60	1'-10	77	72	1'-10	93
** REINFORCING STEEL EPOXY COATED (LBS.)			64,993			71,308			78,076			84,450			91,092			97,529			104,450			110,765			117,372			126,258		
* EPOXY COATING NOT REQUIRED																																
** BARRIER RAIL REINFORCING NOT INCLUDED																																



NOTE: THE REINFORCING STEEL QUANTITY IS TO BE INCLUDED ON THE SUMMARY QUANTITIES SHEET IN THE PLAN.

LATEST REVISION DATE APPROVED BY BRIDGE ENGINEER 	 STANDARD DESIGN - 40' ROADWAY, 3 SPAN BRIDGES <h2 style="margin: 0;">ROLLED STEEL BEAM BRIDGES</h2> OCTOBER, 2014	<h3 style="margin: 0;">DECK AND ABUTMENT REINFORCEMENT 20° SKEW</h3> <h2 style="margin: 0;">RS40-038-14</h2>
---	--	--