



REVISED 10-2016 - CHANGED DIAPHRAGM SPACING IN ZERO SKEW FRAMING PLAN (WAS 4 SPACED AT 18'-0") IN 72'-0" CENTER SPAN. CHANGED DIAPHRAGM SPACING IN SKEWED FRAMING PLAN (WAS 4 SPACED AT 18'-0") IN 72'-0" CENTER SPAN. ADDED DIAPHRAGMS TO SKEWED FRAMING PLAN IN OUTER BAYS, BETWEEN BEAMS 1 & 2 AND 5 & 6 OF 72'-0" CENTER SPAN, 9'-0" FROM PIER CENTERLINES.




0° SKEW FRAMING PLAN



SKEWED FRAMING PLAN
(R.A. SHOWN, L.A. SIMILAR)

NOTE:
DIMENSIONS SHOWN APPLY
AT INTERSECTION OF EXT.
BEAM AND CL DIAPHRAGM



SKEW	a (FT.-IN.)
10°	1'-3 $\frac{1}{2}$ "
20°	2'-8 $\frac{3}{8}$ "
30°	4'-3 $\frac{1}{4}$ "

10-2016 LATEST REVISION DATE	APPROVED BY BRIDGE ENGINEER	STANDARD DESIGN - 40' ROADWAY, 3 SPAN BRIDGES ROLLED STEEL BEAM BRIDGES JUNE, 2010
FRAMING PLAN 180'-0" BRIDGE		RS40-043-10